

QUEL CIP HD

#### 1. Product and company identification **Product name** 5 QUEL CIP HD DuBois Chemicals, Inc. Supplier/Manufacturer 5 3630 E. Kemper Rd. Cincinnati, OH 45241 USA Phone: 1-800-438-2647 DuBois Chemicals Canada, Inc. 1155 North Service Road West Unit 6 Oakville, Ontario, L6M 3E3 Canada Phone: 1-866-861-3603 **Recommended use** : Industrial applications: Liquid caustic detergent **MSDS #** : DUB00884 **Product code** : 12388300, 12388470, 12388100 Validation date : 8/1/2013. Version : 1 : Regulatory Department 1-800-438-2647 **Responsible name** : 1-866-923-4919 (US and Canada) In case of emergency 01-651-523-0314 (Int'l and Mexico) **Hazardous Material** 2 3 Health Information System (U.S.A.) 0 Flammability 1 **Physical hazards**

# 2. Hazards identification

Physical state	: Liquid.
OSHA/HCS status	<ul> <li>This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).</li> </ul>
Emergency overview	: DANGER!
	CORROSIVE. CAUSES DIGESTIVE TRACT, EYE AND SKIN BURNS. MAY CAUSE RESPIRATORY TRACT IRRITATION.
	Do not breathe vapor or mist. Do not ingest. Do not get in eyes or on skin or clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
Routes of entry	: Dermal contact. Eye contact. Inhalation.
Potential acute health effe	<u>cts</u>
Inhalation	<ul> <li>May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. Serious effects may be delayed following exposure.</li> </ul>
Ingestion	: Corrosive to the digestive tract. Causes burns.
Skin	: Corrosive to the skin. Causes burns.
Eyes	: Corrosive to eyes. Causes burns.
Potential chronic health ef	ifects
Carcinogenicity	: No known significant effects or critical hazards.
Target organs	: Contains material which may cause damage to the following organs: upper respiratory tract, skin, eye, lens or cornea.

## 2. Hazards identification

Medical conditions aggravated by overexposure : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (section 11)

3. Composition/information on ingredients		
Name	CAS number	% by weight
sodium hydroxide	1310-73-2	40 - 50

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### 4. First aid measures

Eye contact	<ul> <li>Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.</li> </ul>
Skin contact	<ul> <li>In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.</li> </ul>
Inhalation	: Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
Ingestion	: Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.
Notes to physician	: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

### 5. Fire-fighting measures

Elemmobility of the product	In a fire or if heated, a program increase will easur and the container may hurst	
	In a fire or if heated, a pressure increase will occur and the container may burst.	
Extinguishing media		
Suitable	Use an extinguishing agent suitable for the surrounding fire.	
Not suitable	None known.	
Special exposure hazards	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.	
Hazardous thermal decomposition products	Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides phosphorus oxides metal oxide/oxides	
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breath apparatus (SCBA) with a full face-piece operated in positive pressure mode.	ling

## 6. Accidental release measures

Personal precautions	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
Environmental precautions	: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods for cleaning up	
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

### 7. Handling and storage

Handling

: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from acids. Empty containers retain product residue and can be hazardous. Do not reuse container.

Storage

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## 8. Exposure controls / personal protection

### Occupational exposure limits

Ingredient	Exposure limits
sodium hydroxide	ACGIH TLV (United States, 2/2010). C: 2 mg/m <sup>3</sup> OSHA PEL (United States, 6/2010). TWA: 2 mg/m <sup>3</sup> 8 hour(s).

Consult local authorities for acceptable exposure limits.

Recommended monitoring procedures	:	If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.
Engineering measures	:	If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

# 8. Exposure controls / personal protection

Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Personal protection	
Respiratory	: If a risk assessment indicates this is necessary, use a properly fitted, air-purifying or air- fed respirator complying with an approved standard. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Hands	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
	Recommended: nitrile rubber
Eyes	<ul> <li>Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Recommended: splash goggles</li> </ul>
Skin	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Personal protective equipment (Pictograms)	

# 9. Physical and chemical properties

Physical state	: Liquid.
Flash point	: Closed cup: Not applicable.
Color	: Colorless.
Odor	: Characteristic.
рН	: >14
Dilution pH	: 13.8 [Conc. (% w/w): 1%]
<b>Boiling/condensation point</b>	: Not available.
Melting/freezing point	: Not available.
Specific gravity	: 1.5
Density	: 12.5175 lbs/gal
Vapor pressure	: Not available.
Vapor density	: Not available.
Odor threshold	: Not available.
Evaporation rate	: Not available.
Solubility	: Easily soluble in the following materials: cold water and hot water.
Elemental Phosphorus	: 0.23 %
Octanol/water partition coefficient	: Not available.

# 10. Stability and reactivity

Chemical stability	: The product is stable.
Conditions to avoid	: No specific data.
Materials to avoid	: Reactive or incompatible with the following materials: acids
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.

## 11. Toxicological information

### Acute toxicity

#### **Conclusion/Summary**

QUEL CIP HD : Oral LD50 estimated to be 200 - 1000 mg/kg. Dermal LD50 estimated to be > 2000 mg/kg.

### Carcinogenicity

None known. Acute toxicity estimates

Not available.

#### **Ecological information** 12.

#### **Ecotoxicity**

: No known significant effects or critical hazards.

### Aquatic ecotoxicity

None known.

#### 13. **Disposal considerations**

```
Waste disposal
```

: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any byproducts should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

#### **RCRA classification**

: D002 [Corrosive]

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

#### **Transport** information 14.

IATA/IMDG/DOT/TDG: Please refer to the Bill of Lading/receiving documents for up to date shipping information.

#### **Regulatory information** 15.

### **United States**

ν

U.S. Federal regulations	: TSCA 12(b) one-time export: No products were found. TSCA 12(b) annual export notification: No products were found.	
United States inventory (TSCA 8b)	: All components are listed or exempted.	
	SARA 311/312 MSDS distribution - chemical inventory - hazard identification: QUEL CIP HD: Immediate (acute) health hazard	
	SARA 302/304/311/312 extremely hazardous substances: No products were found	J.
	CERCLA: Hazardous substances.: sodium hydroxide: 1000 lbs. (454 kg);	
alidated on 8/1/2013.	QUEL CIP HD	5

# 15. Regulatory information

### <u>SARA 313</u>

None identified.

#### State regulations

- Massachusetts
- Rhode Island New Jersey

**Pennsylvania** 

- : The following components are listed: SODIUM HYDROXIDE
  - : None of the components are listed.
    - : The following components are listed: SODIUM HYDROXIDE; CAUSTIC SODA
    - : The following components are listed: SODIUM HYDROXIDE (NA(OH))

#### California Prop. 65

None of the components are listed.

#### Canada

- WHMIS (Canada)
- : Class D-1B: Material causing immediate and serious toxic effects (Toxic). Class E: Corrosive material

WHMIS (Pictograms)



### **Canadian lists**

**Canadian NPRI** 

- Canada inventory
- : All components are listed or exempted.

: None of the components are listed.

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

International regulations	
International lists	: Australia inventory (AICS): All components are listed or exempted.
	China inventory (IECSC): All components are listed or exempted.
	Japan inventory: All components are listed or exempted.
	Korea inventory: All components are listed or exempted.
	New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.
	Philippines inventory (PICCS): All components are listed or exempted.
Europe inventory	: All components are listed or exempted.

### 16. Other information

:	
Health	3
Flammability	0
Physical hazards	1
	Flammability

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

Date of issue	: 8/1/2013.
Date of previous issue	: No previous validation.
Version	: 1
Indicator information the	t has changed from proviously is

Indicates information that has changed from previously issued version.

#### Notice to reader

# 16. Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.